1U 17" LCD KVM CONSOLE



- Monitor, keyboard and mouse storage area in 1U of rack space for 19" racks.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.

17" Diagonal

31.5 to 80 KHz

56 to 75 Hz

Horizontal Frequency:

Vertical Frequency:

- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan™ covering.
- Available with Cherry™ keyboard.

DISPLAY SPECIFICATIONS

Display Type: Resolution: Active matrix TFT LCD 640 x 350 Colors: 640 x 480 16.7 million colors 800 x 600 **Contrast Ratio:** 1024 x 768 1000:1 typ 1280 x 1024 **Brightness:** Display Area:

250 cd/m² typ Viewing Angle:

> Horizontal: 170° Vertical: 160°

KEYBOARD SPECIFICATIONS

Response Time: 25ms

Rollover:

Auto repeat: Self Diagnostics:

Data Buffer:

Operating voltage:

Operating current:

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 1.75" (H) x 25.75" (D)

Weight:

27 lbs

Power (TFT Display):

100 - 240 VAC, 50/60 Hz 60 Watts maximum

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical

Position, Auto Adjust, OSD H & V Position, Load

and Save Values

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 0°C to 50°C Storage: -20°C to 60°C

Humidity:

Operating: 10 to 85% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync

Input Connector:

Display: 15-pin mini D-Shell

Color:

Black

Interface: USB, or optional PS/2 (P) Keyboard: Compatibility: Windows operating systems

Optional Mouse (M): Optional optical mouse, USB

Alpha N-key rollover

+5 VDC +/- 5%

100 mA (max)

At power on and system reset

All codes buffered before sending

Specifications subject to change without notice.

MODEL NUMBER

RMM-2X7XXX

We offer OEM and custom solutions. Contact us for additional information.



Blank = No Mouse M = USB Mouse Standard Keyboard = 1 Cherry™ Keyboard = 2 -Blank = Standard Front Panel R = Front Panel + Retainer Screws Blank = USB L = Front Panel + Lock P = PS/2C = Front panel + Lock + Retainer Screw



www.recortec.com