1U 17" LCD KVM CONSOLE





- Monitor and Cherry™ keyboard with trackball in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan[™] covering.

DISPLAY SPECIFICATIONS

Display Type: Active matrix TFT LCD Colors: 16.7 million colors Contrast Ratio: 1000:1 typ Brightness: 280 cd/m² typ Viewing Angle: Horizontal: 170° Vertical: 160° Response Time: 25ms
 Resolution:
 640 x 350

 640 x 480
 800 x 600

 1024 x 768
 1280 x 1024

 Display Area:
 17" Diagonal

 Horizontal Frequency:
 31.5 to 80 KHz

 Vertical Frequency:
 56 to 75 Hz

KEYBOARD AND MOUSE SPECIFICATIONS

Rollover: Auto repeat: Self Diagnostics: Data Buffer: Operating voltage: Operating current: Trackball Size: Touchpad Size: Buttons: Interface: Compatibility: Alpha N-key rollover Yes At power on and system reset All codes buffered before sending +5 VDC +/- 5% 100 mA max 16mm 2.1" X 1.25" Left and Right USB, or optional PS/2 (P) Windows operating systems

Specifications subject to change without notice.


We offer OEM and custom solutions. Contact us for additional information.



GENERAL SPECIFICATIONS

Dimensions: 19.0" (W) x 1.75" (H) x 20.80" (D) Weight: 25 lbs Power (TFT Display): 90 - 260 VAC, 50/60 Hz 60 Watts maximum **On-Screen Controls:** Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values Plug & Play: DDC1 and DDC2B **Temperature:** 0°C to 50°C Operating: Storage: -20°C to 60°C Humidity: Operating: 10 to 85% RH (max) Input Signal (VGA): R.G.B. analog video, TTL H & V sync Input Connector: Display: 15-pin mini D-Shell Color: Black

MODEL NUMBER





www.recortec.com

sales@recortec.com

 2231-A Fortune Drive
 Tel: 408-928-1480

 San Jose, CA 95131
 Fax: 408-928-1489

