

# 19" RACK MOUNT LCD MONITOR



- IPS Display features wide H/V viewing angles.
- 19" LCD display with 1280 x 1024 resolution.
- Mounts in 8U (14.0") of vertical 19" rack space.
- Steel front panel construction with a durable powder coat finish.
- LED Backlight provides high contrast ratios and energy savings.
- Analog and Digital inputs.

## GENERAL SPECIFICATIONS

- Dimensions:**  
19.0" (W) x 14.0" (H) x 2.4" (D)
- Weight:**  
8.75 lbs.
- Power:**  
100 - 240 VAC, 50/60 Hz.  
18 Watts typ.
- On-Screen Controls:**  
Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Input Select Color Temp., Reset.
- Plug & Play:**  
DDC/C1
- Temperature:**  
Operating: 10°C to 40°C  
Storage: -20°C to 45°C
- Humidity:**  
Operating: 10 to 80% RH (max)
- Input Signal (VGA):**  
R.G.B. analog video, TTL H & V sync.
- Input Signal (Digital):**  
DVI-D (HDCP).
- Input Connectors:**  
Analog: 15-pin mini D-Sub.  
Digital: 24 pin DVI-D.
- Colors Available:**  
Black.

## DISPLAY SPECIFICATIONS

- Display Type:**  
Active matrix TFT LCD
- Display area:**  
19.0" Diagonal.
- Colors Displayed:**  
16.7 million colors.
- Contrast Ratio:**  
1000:1 / 5M:1 DFC
- Brightness:**  
250 cd/m<sup>2</sup> typ.
- Backlight:**  
LED 4 Channel

- Viewing Angle:**  
Horizontal: 178°  
Vertical: 178°
- Response Time:**  
5ms
- Resolution:**  
VGA up to 1280 x 1024.
- Color Gamut (CIE1976):**  
72%
- Horizontal Frequency:**  
30 to 83 KHz.
- Vertical Frequency:**  
56 to 75 Hz.

Specifications subject to change without notice.

## MODEL NUMBER

- RMM-409N3**  
**RMM-409N3/L (with Lexan™ screen protection)**

Offering OEM and custom solutions.  
Contact us for additional information.



**RECORTEC, INC.**

www.recortec.com  
sales@recortec.com

**1-800-729-7654**

3329 Kifer Road Tel: 408-928-1480  
Santa Clara, CA 95051 Fax: 408-928-1489