

# 19" 16:10 FORMAT MONITOR



- Mounts in 7U of 19" rack space.
- Wide format 16:10 aspect ratio.
- Fast 5 ms response time.
- 19" TFT LCD display with 1440 x 900 resolution.
- Analog (ARGB) and Digital (DVI-D) input connectors.
- Energy saving LED backlight.

## GENERAL SPECIFICATIONS

- Dimensions:**  
19.0" (W) x 12.25" (H) x 2.8" (D)
- Weight:**  
8.5 lbs.
- Power:**  
100 - 240 VAC, 50/60 Hz.  
30 Watts.
- On-Screen Controls:**  
Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Input Select Color Temp., Reset.
- Plug & Play:**  
DDC2B
- Temperature:**  
Operating: 10°C to 40°C  
Storage: -20°C to 45°C
- Humidity:**  
Operating: 10 to 80% RH (max)
- Input Signal (VGA):**  
R.G.B. analog video, TTL H & V sync.
- Input Signal (Digital):**  
DVI with HDCP.
- Input Connectors:**  
Analog: 15-pin mini D-Sub.  
Digital: 24 pin DVI-D.
- Colors Available:**  
Black.

## DISPLAY SPECIFICATIONS

- Display Type:**  
Active matrix TFT LCD
- Display area:**  
19" Wide.
- Colors Displayed:**  
16.7 million colors.
- Contrast Ratio:**  
1,000:1 (5M:1 Dynamic)
- Brightness:**  
250 cd/m<sup>2</sup> typ.
- Viewing Angle:**  
Horizontal: 170°  
Vertical: 160°
- Response Time:**  
5 ms.
- Resolution:**  
Up to 1440 x 900.
- Aspect Ratio:**  
16:10.
- Backlight type:**  
LED

Specifications subject to change without notice.

## MODEL NUMBER

- RMM-419N2**  
**RMM-419N2L** with Lexan™ Screen Protection

*Contact us about other options and our additional rack mount products.*



**RECORTEC, INC.**

www.recortec.com  
sales@recortec.com

**1-800-729-7654**

3329 Kifer Road Tel: 408-928-1480  
Santa Clara, CA 95051 Fax: 408-928-1489