23” 16:9 FULL HD MONITOR

- Mounts in 8U of rack space with mounting brackets to fit 19” rack width.
- 23” Wide format TFT LCD display with full HD 1920 x 1080 resolution.
- LED backlight and super wide *178/178 degree viewing angles*.
- 1080p 16:9 aspect ratio provides a widescreen viewing area.
- 5,000,000:1 Dynamic contrast ratio for superior detail.
- EPEAT Gold Rated, Energy Star 5.0 & RoHS Compliant.

GENERAL SPECIFICATIONS

Dimensions:
22.75" (W) x 14.0" (H) x 3.0" (D)
Weight:
17.0 lbs.
Power:
100 - 240 VAC, 50/60 Hz.
32 Watts typ.
Plug & Play:
DDC2B
Temperature:
Operating: 0°C to 40°C
Storage: -20°C to 45°C
Humidity:
Operating: 20 to 90% RH (non-condensing)
Input Video Signals:
R.G.B. analog, DVI (with HDCP)
Input Frequency:
Fh: 30-83 KHz, Fv: 56-75 Hz.
Sync Type:
Separate H/V, Composite H/V, SOG.
Input Connectors:
15 pin D-sub, DVI-D.
Compatibility:
PC/Windows, Macintosh.
Colors Available:
Black.

Offering OEM and custom solutions.
Contact us for additional information.

DISPLAY SPECIFICATIONS

Display Type:
TFT active matrix with IPS LCD.
Viewable Size:
23.0” diagonal.
Colors Displayed:
16.7 million colors.
Contrast Ratio (Typ/Dyn):
1000:1 / 5,000,000:1
Brightness:
250 cd/m² typ.
Viewing Angles:
178°/178° H/V.
Response Time:
5 ms Typ.
Optimum Resolution
1920 x 1080 non-interlaced.
Light Source:
LED
Panel Surface:
Anti-glare.

Specifications subject to change without notice.

MODEL NUMBER

RMM-423HD1

RMM-423HD1L with Lexan™ Screen Protection

RMM-423HD1 shown mounted in a standard 19” equipment rack.

RECORTEC, INC.
www.recortec.com
sales@recortec.com
1-800-729-7654
3329 Kifer Road
Santa Clara, CA 95051
Tel: 408-928-1480
Fax: 408-928-1489