

1U 17" LCD KVM CONSOLE



- Monitor, keyboard, 1.5" 3 button illuminated trackball in 1U of rack space.
- Mounted with included ball bearing slides which lock in the extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Monitor surface protected by a clear unbreakable Lexan™ covering.
- Available with Cherry™ keyboard.

DISPLAY SPECIFICATIONS

Display Type:	Active matrix TFT LCD	Resolution:	640 x 350 640 x 480 800 x 600 1024 x 768 1280 x 1024
Colors:	16.7 million colors	Display Area:	17" Diagonal
Contrast Ratio:	1000:1 typ	Horizontal Frequency:	31.5 to 80 KHz
Brightness:	250 cd/m ² typ	Vertical Frequency:	56 to 75 Hz
Viewing Angle:	Horizontal: 170° Vertical: 160°		
Response Time:	5ms		

KEYBOARD AND TRACKBALL SPECIFICATIONS

Rollover:	Alpha N-key rollover
Auto repeat:	Yes
Self Diagnostics:	At power on and system reset
Data Buffer:	All codes buffered before sending
Operating voltage:	+5 VDC +/- 5%.
Operating current:	200 mA
Trackball Size:	1.5" Illuminated (optical sensor)
Buttons:	Left, Lock and Right
Trackball Color:	Blue (illuminated when powered)
Interface:	USB, or optional PS/2 (P)
Compatibility:	Windows operating systems
Optional Cherry™ Keyboard:	Add suffix "K" to part number (K)

Specifications subject to change without notice.

We offer OEM and custom solutions.
Contact us for additional information.



GENERAL SPECIFICATIONS

Dimensions:	19.0" (W) x 1.75" (H) x 25.75" (D)
Weight:	27 lbs
Power (TFT Display):	90 - 260 VAC, 50/60 Hz. 60 Watts maximum
On-Screen Controls:	Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values
Plug & Play:	DDC1 and DDC2B
Temperature:	Operating: 0°C to 50°C Storage: -20°C to 60°C
Humidity:	Operating: 10 to 85% RH (max)
Input Signal (VGA):	R.G.B. analog video, TTL H & V sync
Input Connector:	Display: 15-pin mini D-Shell
Color:	Black

MODEL NUMBER

RMM-617TXXX

Blank = Std Kybd	Blank = Standard Front Panel
K = Cherry™ Kybd	R = Front Panel + Retainer Screws
	L = Front Panel + Lock
	C = Front panel + Lock + Retainer Screw
	Blank = USB
	P = PS/2

RECORTEC

www.recortec.com
sales@recortec.com

2231-A Fortune Drive Tel: 408-928-1480
San Jose, CA 95131 Fax: 408-928-1489