

2U 17" LCD KVM CONSOLE



Optional Light Gray (W) color shown



- Monitor and keyboard with two button touchpad in 2U of rack space for mounting in 19" racks.
- Included adjustable mounting depth ball bearing slides lock in the fully extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Reduced rack depth for mounting in confined spaces.

DISPLAY SPECIFICATIONS

| | | | |
|-----------------------------|----------------------------|------------------------------|--------------|
| Display Type: | Active matrix TFT LCD | Resolution: | 640 x 350 |
| Colors: | 16.7 million colors | | 640 x 480 |
| Contrast Ratio: | 1000:1 typ. | | 800 x 600 |
| | | | 1024 x 768 |
| | | | 1280 x 1024 |
| Brightness: | 250 cd/m ² typ. | Display Area: | 17" Diagonal |
| Viewing Angle: | | Horizontal Frequency: | 31 to 80 KHz |
| Horizontal: | 170° | Vertical Frequency: | 55 to 76 Hz |
| Vertical: | 160° | | |
| Response Time (TYP): | 5ms | | |

KEYBOARD AND TOUCHPAD SPECIFICATIONS

| | |
|---------------------------|-----------------------------------|
| Rollover: | Alpha N-key rollover |
| Auto repeat: | Yes |
| Self Diagnostics: | At power on and system reset |
| Data Buffer: | All codes buffered before sending |
| Operating voltage: | +5 VDC +/- 5% |
| Operating current: | 200 mA |
| Touchpad Size: | 2.2" X 1.6" |
| Buttons: | Left and Right |
| Interface: | USB, or optional PS/2 (P) |
| Compatibility: | Windows operating systems |

Specifications subject to change without notice.

GENERAL SPECIFICATIONS

| | |
|-----------------------------|---|
| Chassis Dimensions: | 19.0" (W) x 3.50" (H) x 13.25" (D) |
| Weight: | 20 lbs |
| Power (TFT Display): | 90 - 260 VAC, 50/60 Hz. 60 Watts maximum |
| On-Screen Controls: | Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values |
| Plug & Play: | DDC1 and DDC2B |
| Temperature: | Operating: 0°C to 50°C Storage: -20°C to 60°C |
| Humidity: | Operating: 10 to 85% RH (max) |
| Input Signal (VGA): | R.G.B. analog video, TTL H & V sync |
| Input Connector: | Display: 15-pin mini D-Shell |
| Colors Available: | Black, Light Gray (W) |

MODEL NUMBER

RMM-817XXX

| | |
|---|---|
| — | Blank = Standard Front Panel |
| — | R = Front Panel + Retainer Screws |
| — | L = Front Panel + Lock |
| — | C = Front Panel + Lock + Retainer Screw |
| — | Blank = USB |
| — | P = PS/2 |
| — | Blank = Black |
| — | W = Light Gray |

We offer OEM and custom solutions.
Contact us for additional information.



RECORTEC

www.recortec.com
sales@recortec.com

2231-A Fortune Drive Tel: 408-928-1480
San Jose, CA 95131 Fax: 408-928-1489