

# 2U 17" LCD KVM CONSOLE



- Monitor, keyboard and storage/use area for mouse occupies 2U of 19" rack space.
- Included adjustable mounting depth ball bearing slides lock in the fully extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Reduced rack depth for mounting in confined spaces.
- Available with Cherry™ keyboard.

## DISPLAY SPECIFICATIONS

<b>Display Type:</b>	Active matrix TFT LCD	<b>Resolution:</b>	640 x 350 640 x 480 800 x 600 1024 x 768 1280 x 1024
<b>Colors:</b>	16.7 million colors	<b>Display Area:</b>	17" Diagonal
<b>Contrast Ratio:</b>	1000:1 typ.	<b>Horizontal Frequency:</b>	31 to 80 KHz
<b>Brightness:</b>	250 cd/m <sup>2</sup> typ.	<b>Vertical Frequency:</b>	55 to 76 Hz
<b>Viewing Angle:</b>	Horizontal: 170° Vertical: 160°		
<b>Response Time (TYP):</b>	5ms		

## KEYBOARD SPECIFICATIONS

<b>Rollover:</b>	Alpha N-key rollover
<b>Auto repeat:</b>	Yes
<b>Self Diagnostics:</b>	At power on and system reset
<b>Data Buffer:</b>	All codes buffered before sending
<b>Operating voltage:</b>	+5 VDC +/- 5%
<b>Operating current:</b>	100 mA (max)
<b>Interface:</b>	Keyboard: USB, optional PS/2 (P)
<b>Compatibility:</b>	Windows operating systems
<b>Optional Mouse (M):</b>	Optional optical mouse, USB
<b>Optional Cherry™ Keyboard:</b>	Add suffix "K" to part number (K)

Specifications subject to change without notice.

We offer OEM and custom solutions.  
Contact us for additional information.



Blank = Std Kybd  
K = Cherry™ Kybd

## GENERAL SPECIFICATIONS

<b>Chassis Dimensions:</b>	19.0" (W) x 3.50" (H) x 13.25" (D)
<b>Weight:</b>	20 lbs
<b>Power (TFT Display):</b>	90 - 260 VAC, 50/60 Hz 60 Watts maximum
<b>On-Screen Controls:</b>	Brightness, Contrast, Horizontal & Vertical Position, Auto Adjust, OSD H & V Position, Load and Save Values
<b>Plug &amp; Play:</b>	DDC1 and DDC2B
<b>Temperature:</b>	Operating: 0°C to 50°C Storage: -20°C to 60°C
<b>Humidity:</b>	Operating: 10 to 85% RH (max)
<b>Input Signal (VGA):</b>	R.G.B. analog video, TTL H & V sync
<b>Input Connector:</b>	Display: 15-pin mini D-Shell
<b>Colors Available:</b>	Black

## MODEL NUMBER

RMM-867XXXX

Blank = No Mouse	Blank = Std Kybd
M = USB Mouse	K = Cherry™ Kybd
Blank = Standard Front Panel	
R = Front Panel + Retainer Screws	
L = Front Panel + Lock	
C = Front Panel + Lock + Retainer Screw	
Blank = USB	
P = PS/2	

**RECORTEC**

www.recortec.com  
sales@recortec.com

2231-A Fortune Drive Tel: 408-928-1480  
San Jose, CA 95131 Fax: 408-928-1489