

2U 17" AND 19" LCD KVM CONSOLES



- Monitor, keyboard and storage/use area for mouse occupies 2U of 19" rack space.
- Included adjustable mounting depth ball bearing slides lock in the fully extended position.
- Monitor powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Reduced rack depth for mounting in confined spaces.

DISPLAY SPECIFICATIONS

Display Type:
Active matrix TFT LCD

Colors:
16.7 million colors

Contrast Ratio:
17": 1000:1 typ.
19": 800:1 typ.

Brightness:
17": 250 cd/m² typ.
19": 270 cd/m² typ.

Viewing Angle: 17" 19"
Horizontal: 170° 178°
Vertical: 160° 178°

Response Time (TYP):
5ms 18ms

Resolution:
640 x 350
640 x 480
800 x 600
1024 x 768
1280 x 1024

Display Area:
17" - 17" Diagonal
19" - 19" Diagonal

Horizontal Frequency:
31 to 80 KHz

Vertical Frequency:
55 to 76 Hz.

KEYBOARD SPECIFICATIONS

Rollover: Alpha N-key rollover.

Auto repeat: Yes.

Self Diagnostics: At power on and system reset.

Data Buffer: All codes buffered before sending.

Operating voltage: +5 VDC +/- 5%.

Operating current: 100 mA (max).

Interface: Keyboard: PS/2 or USB (U).

Compatibility: Windows operating systems.

Optional Mouse (M): Optional optical mouse, PS/2 or USB (U).

Optional Cherry™ Keyboard: Add suffix "C" to part number (C).

Specifications subject to change without notice.

We offer OEM and custom solutions.
Contact us for additional information.



GENERAL SPECIFICATIONS

Chassis Dimensions:
17": 19.0" (W) x 3.50" (H) x 13.25" (D)
19": 19.0" (W) x 3.50" (H) x 14.90" (D)

Weight:
20 lbs

Power (TFT Display):
90 - 260 VAC, 50/60 Hz.
60 Watts maximum

On-Screen Controls:
Brightness, Contrast, Horizontal & Vertical
Position, Auto Adjust, OSD H & V Position, Load
and Save Values

Plug & Play:
DDC1 and DDC2B

Temperature:
Operating: 0°C to 50°C
Storage: -20°C to 60°C

Humidity:
Operating: 10 to 85% RH (max)

Input Signal (VGA):
R.G.B. analog video, TTL H & V sync.

Input Connector:
Display: 15-pin mini D-Shell

Colors Available:
Black(B) and Light Gray.

MODEL NUMBER

RMM-86(X)(X)

- Blank = Standard Front Panel
- R = Front Panel + Retainer Screws
- L = Front Panel + Lock
- C = Front Panel + Lock + Retainer Screw
- 7 = 17" TFT Display
- 9 = 19" TFT Display

RECORTEC, INC.

www.recortec.com
sales@recortec.com

1-800-729-7654

3329 Kifer Road Tel: 408-928-1480
Santa Clara, CA 95051 Fax: 408-928-1489