

# 19" RACK MOUNT LCD MONITOR



- 19" TFT LCD display (1280 x 1024 resolution) in only 8U (14.0") of rack space.
- Removable rack mounting brackets allow for additional mounting options.
- Wide Horizontal and Vertical viewing angles offer viewing flexibility.
- Controls mounted on side of monitor for a clean appearance.
- Optional Lexan™ (L) or 5 wire resistive touchscreen (T).
- VGA, DVI-D, and HDMI Inputs.

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 14.0" (H) x 1.7" (D)  
1.7" (D) = 0.75" in front of mounting rails  
0.95" behind mounting rails

### Weight:

11 lbs

### Power:

110 - 240 VAC, 50/60 Hz  
60 Watts max

### On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical  
Position, Auto Adjust, OSD H & V Position, Input Select  
Color Temp, Reset

### Plug & Play:

DDC1 and DDC2B

### Temperature:

Operating: 0°C to 50°C  
Storage: -20°C to 60°C

### Humidity:

Operating: 10 to 90% RH (max)

### Input Signal (VGA):

R.G.B. analog video, TTL H & V sync

### Input Signal (Digital):

DVI-D (TDMS), HDMI

### Input Connectors:

Analog: 15-pin mini D-Sub  
Digital: 24 pin DVI-D, HDMI

### Colors Available:

Black

## DISPLAY SPECIFICATIONS

### Display Type:

Active matrix TFT LCD

### Display area:

19" Diagonal

### Colors Displayed:

16.7 million colors

### Contrast Ratio:

800:1 typ

### Brightness:

270 cd/m<sup>2</sup> typ

### Viewing Angle:

Horizontal: 178°  
Vertical: 178°

### Response Time:

18ms Typ

### Resolution:

VGA up to 1280 x 1024

### Horizontal Frequency:

31 to 80 KHz

### Vertical Frequency:

55 to 76 Hz

### Screen Protection:

Optional Lexan™ (L) or  
5 Wire Resistive  
Touchscreen (T)

Specifications subject to change without notice.

## MODEL NUMBER

### RMM-909X

— L = Lexan™ Screen Protection  
— T = 5 Wire Resistive Touchscreen



Offering OEM and custom solutions.  
Contact us for additional information.

# RECORTEC

www.recortec.com

sales@recortec.com

2231-A Fortune Drive, San Jose, CA 95131

Tel: 408-928-1480