

# RACK MOUNT SPEAKERS



## 1U Rack Mount Speaker

The RSS-125 speaker system is a fully enclosed amplified stereo speaker system featuring front panel controls which include a Power ON/OFF and Volume Control Switch with Power Indicator. The front panel Headphone Jack disables the internal speakers when a headphone plug is inserted, directing audio output to the headphones. A front panel 3.5mm AUX input jack overrides the rear input source allowing connection of a second source. The unit is supplied with a detachable audio cable and an external 100-240 VAC 50/60 Hz input power supply (optional 110/220 VAC 50/60 Hz input power supply with universal power cord NEMA 5-15P to IEC320C13).



Rear View - Standard Power Supply



Rear View - Optional Power Supply

## MODEL NUMBER

**RSS-125X**

- Blank = Standard Power Supply
- U = 110/220V Power Supply with NEMA 5-15P to IEC320C13 power cord



We offer OEM and custom solutions.  
Contact us for additional information.

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 1.75" (H) x 3.5" (D)

### Weight:

3.7 lbs

### Power Supply:

Standard - 100-240 VAC, 50/60 Hz.

Optional - 110/220 VAC, 50/60 Hz with NEMA 5-15P to IEC320C13 power cord.

### Colors Available:

Black.

### Front Panel Controls:

Power ON/OFF switch, Volume Control, Headphone Jack, Power Indicator.

### Audio Amplifier Output:

12 Watts.

### Audio Input Connector:

1/8" (3.5mm) stereo jack.

Specifications subject to change without notice.

**RECORTEC, INC.**

[www.recortec.com](http://www.recortec.com)

[sales@recortec.com](mailto:sales@recortec.com)

2231-A Fortune Drive  
San Jose, CA 95131

Tel: 408-928-1480  
Fax: 408-928-1489